

# PR Series Pancake Slip Rings

### SLIP RING



# **Product Features**

- Extremely thin, save space
- Separate type and two-in-one structure


# Typical application

- Military equipment
- Yatch
- 3D total station

# Options

- Installation way: Integral or separate type
- Lead wire length

### Installation



Customised Parameters		
Model	Parameters	Dimensions ( mm )
PR031-10P	Inner Diameter: 31mm (optional) Protection (IP Grade): IP54/optional Rating Voltage: 380V Working Temperature: -20°C to +80°C Working Humidity: 60%RH Dielectric Strength: ≥500V@50Hz Working Speed: 0 - 300RPM Current: 10 * 2A (optional) Electrical Noise: <70mΩ (50rpm) Contact Material: Gold and gold Installation: The rotor end - customer's spindle through coupling	Rotor Side Stator Side Anti-Rotation Tab
PSR000-02 P2-02S	Inner Diameter: 0mm (optional) outer Diameter: 72mm (optional) Rating Voltage: 380V Working Temperature: -20°C to +80°C Working Humidity: 60%RH Dielectric Strength: ≥500V@50Hz Working Speed: 0 - 300RPM Current: 2 * 10A	## ## ## ## ## ## ## ## ## ## ## ## ##

Custom design and specifications may be available upon request. Please contact us for details.